

USE AND MAINTENANCE FOR SHORE POWER INLETS

USE

1. Turn off the boat's shore connection switch before connecting or disconnecting shore power cable.
2. Connect shore power cable at the boat first.
3. If polarity warning indicator is activated, immediately disconnect cable and have the fault corrected by qualified electrician.
4. Disconnect shore power cable at shore outlet/receptacle first.

MAINTENANCE

(Always disconnect from power source before performing maintenance).

General:

The metallic parts of your MARINCO inlet are made to resist corrosion. In salt water environment, life of the product can be increased by periodically wiping the exposed parts with fresh water, drying and spraying with a moisture repellent.

In case of Salt Water Spray or Immersion:

Rinse interior thoroughly in fresh water, wipe away excess water with a clean, dry towel and allow to dry. Spray with a moisture repellent before re-use.

INSTRUCTION SHEET

SHORE POWER CABLE SET

USE

1. Turn off the boat's shore connection switch before connecting or disconnecting shore power cable.
2. Connect shore power cable at the boat first.
3. If polarity warning indicator is activated, immediately disconnect cable and have the fault corrected by qualified electrician.
4. Disconnect shore power cable at shore outlet/receptacle first.

STORAGE

Your MARINCO shore power cable set is intended for use outdoors. To prolong the life of the set, store indoors when not in use.

MAINTENANCE

(Always disconnect from power source before performing maintenance).

General:

The metallic parts of your MARINCO cable set are made to resist corrosion. In salt water environment, life of the product can be increased by periodically wiping the exposed parts with fresh water, drying and spraying with a moisture repellent.

A soiled cable can be cleaned with grease cutting household detergent. A periodic application of vinyl protector will help both ends and cable maintain their original appearance.

In case of Salt Water Immersion:

Rinse plug end and/or connector end thoroughly in fresh water, shake or blow out excess water and allow to dry. Spray with a moisture repellent before re-use.

REPAIR

If either plug or connector end requires replacement (component or molded type), it can be replaced with the following MARINCO devices:

<u>CABLE RATING</u>	<u>PLUG</u>	<u>COVER</u>	<u>CONNECTOR</u>	<u>COVER</u>
30A-125V 2 pole, 3 wire	305CRP	102	305CRC	103R
50A-125V 2 pole, 3 wire	6361CR	7717	6360CR	7715CR
50A-125/250V 3 pole, 4 wire	6365CR	7717	6364CR	7715CR

MARINCO recommends that this Instruction Sheet be made a part of your Boat Service Manual.