



Caterpillar 3208 Marine Engine Zinc Anodes

There are two different heat exchangers used by 3208 marine engines, 4W-9164 and 7C-3114, and each requires a different zinc anode configuration:

- 4W-9164 Engine Heat Exchanger

Qty 2 6L-2283 (E-0A)

Located on port side bonnet

Qty 1 6L-2283 (E-2B)

Located on starboard side bonnet

Tech Support 3208's

2 - 1/4npt 3/8 x 2 1/2"

1 - 1/2npt 5/8 x 3"

- 7C-3114 Engine Heat Exchanger

Qty 2 6L-2283 (E-0A)

Located on port side bonnet

Qty 1 6L-2283 (E-0A)

Located on starboard side bonnet

3 - 1/4npt 3/8 x 2 1/2"

The 7W-1396 3208 Marine Transmission Oil Cooler requires the following:

Qty 2 6L-2288 (E-2)

Located on each side of unit

2 - 1/2" npt 5/8 x 2"

Note: Some 3208 marine transmission oil coolers have no anodes.

The 5N-6447 Water Cooled Exhaust Elbow requires the following:

Qty 1 6L-2016 (E-3A)

1 - 3/4 npt 3/4 x 3/4"

The 6N-0011 Water Cooled Exhaust Elbow Group requires the following:

Qty 2 6L-2016 (E-3A)

Note: Some 3208 marine exhaust elbows operate dry and have no anodes.

Westerbeke 8BTA 8kw diesel

1 - 1/4npt 3/8 x 2 1/2"